



# SEW150

100% Polyester

White  
Weiss2,0/2,2  
Decitex0,56  
mm0,09  
%240  
gramMD 512,4 N/5cm Length  
CD 518,3N/5cm cross

## FILTER MEDIA DATA

SEW 150 is a 100% spun bond filters media that is manufactures from continuous fibre who does not permit the particles to become embedded.

SEW 150 is very rugged and have a high burst strength that make it resistant to abrasion water, heat and chemicals.

100 % Spun bond media makes pulse cleaning easier and are running with lower pressure drop  
SEW 150 is a washable filter media.

Dry  
Trocken

120 Celsius

Wet  
Feuchte

90 Celsius

Air Permeability | 200Pa  
Luftdurchlässigkeit | 200Pa

490 m3/m2/hr

## Chemical Resistance | Chemische Eigenschaften

|                                                 | Excellent<br>Sehr Gut | Good<br>Gut | Fair<br>Mässig |
|-------------------------------------------------|-----------------------|-------------|----------------|
| Oil/water resistance<br>Öl und Wasserabweisend  | X                     | X           | X              |
| Hydrolysis resistance<br>Hydrolysebeständigkeit | X                     | X           | X              |
| Acid resistance<br>Säurebeständigkeit           | X                     | X           | X              |
| Alkaline resistance<br>Alkalienbeständigkeit    | X                     | X           | X              |



Phone +45 5460 2080



Certificate No.

S.E.W. North Filtration A/S \* Vesterbrogade1, Section C \* DK-4930 Maribo  
E-mail: sales@northfiltration.com \* www.northfiltration.com \* VAT no.: DK 33 49 28 71